

View Online at <https://aerobasegroup.com/nsn/3020-00-322-9624>

Counterbore Diameter:

Between 2.125 inches and 2.375 inches

Counterbore Depth:

Between 0.500 inches and 0.563 inches

Groove Depth:

0.422 inches

Groove Width:

Between 0.365 inches and 0.385 inches

Outside Diameter:

7.125 inches

Overall Length:

3.563 inches

Key Width:

Between 0.251 inches and 0.253 inches

Bore Diameter:

Between 1.7495 inches and 1.7505 inches

Bore Length:

2.625 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.997 inches and 1.002 inches

Drilled Hole Diameter:

0.406 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

6.703 inches

Securing Hole Quantity:

4

Material And Location:

Iron, cast, qq-i-652, class 30

Face Width:

2.094 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

4

Counterbore Feature:

Included

Counterbore Location:

Bb end

Hole Location:

Located on face of hub

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Drilled hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Aa end

First Step Face Largest Diameter And Location:

2.599 inches aa end and 2.619 inches aa end

First Step Length And Location:

1.438 inches aa end

Hub End Outside Diameter And Location:

2.375 inches aa end and 2.746 inches bb end and 2.748 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

1.469 inches aa end and 0.938 inches bb end

Special Features:

W/two dowel pins 3/8 in. Diameter by 1-1/2 in. Long pressed into 0.3699 in. Min, 0.3709 in. Maximum diameter holes

Quantity:

1

Surface Treatment:

Phosphate

Style Designator:

Webbed or spoked

Surface Treatment:

Phosphate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a