NSN 3020-00-328-8179

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-328-8179

Body Style:

Plain, solid

Pitch Diameter:

0.8571 inches

Teeth Quantity:

24

Bore Style:

Partial both ends

Outside Diameter:

0.9260 inches

Tooth Form:

Standard

Pressure Angle:

25.0000 degrees

Distance Between Body Face And Protruding Hub End:

2.4930 inches first end

Face Width:

0.175 inches

Bore Diameter:

0.4400 inches both ends

Bore Depth:

2.970 inches both ends

Hub Style Designator:

2 steps first end

End Length:

1.2220 inches second end

Precision Classification:

Is0 precision class 1

End Diameter:

0.6247 inches first end

First Step Length:

2.0830 inches first end

First Step Diameter:

0.7900 inches second end

Second Step Length:

0.0100 inches first end

Second Step Diameter:

0.7900 inches first end

Special Features:

Spline on end of hub

Material:

Aluminum alloy 7075

NSN 3020-00-328-8179

Spur Gear - Page 2 of 2



Material Specification:

Qq-a-225/9, t73 federal specification single material response and qq-a-225/9, t651 federal specification single material response and

qq-a-225/11, t73 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.