NSN 3020-00-328-8179

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-328-8179

Body Style:
Plain, solid
Pitch Diameter:
0.8571 inches
Teeth Quantity:
24
Bore Style:
Partial both ends
Outside Diameter:
0.9260 inches
Tooth Form:
Standard
Pressure Angle:
25.0000 degrees
Distance Between Body Face And Protruding Hub End:
2.4930 inches first end
Face Width:
0.175 inches
Bore Diameter:
0.4400 inches both ends
Bore Depth:
2.970 inches both ends
Hub Style Designator:
2 steps first end
End Length:
1.2220 inches second end
Precision Classification:
Is0 precision class 1
End Diameter:
0.6247 inches first end
First Step Length:
2.0830 inches first end
First Step Diameter:
0.7900 inches second end
Second Step Length:
0.0100 inches first end
Second Step Diameter:
0.7900 inches first end
Special Features:
Spline on end of hub
Material:
Aluminum alloy 7075

NSN 3020-00-328-8179

Spur Gear - Page 2 of 2



Material Specification:

Qq-a-225/9, t73 federal specification single material response and qq-a-225/9, t651 federal specification single material response and qq-a-225/11, t73 federal specification single material response

ο.				•			4 -
ગ	ırt	ac	e T	re	atr	ne	nt:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.