## NSN 3020-00-330-0512

Spur Gear - Page 1 of 2

**Mounting Hole Diameter:** 

0.187 inches axially through body, first end



View Online at https://aerobasegroup.com/nsn/3020-00-330-0512

Body Style:
Plain, with lightening holes
Attachment Method:
Mounting hole
Pitch Diameter:
3.4375 inches
Teeth Quantity:
110
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thread Size:
0.187 inches axially through body, first end
Mounting Hole Type And Quantity:
3 plain axially through body, first end and 3 threaded axially through body, first end
Outside Diameter:
3.4985 inches
Tooth Form:
Standard
Pressure Angle:
Pressure Angle: 20.0000 degrees
20.0000 degrees
20.0000 degrees  Distance Between Body Face And Protruding Hub End:
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:  Plain second end
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:  Plain second end  Hub Diameter:
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:  Plain second end  Hub Diameter:  1.0625 inches second end
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:  Plain second end  Hub Diameter:  1.0625 inches second end  Precision Classification:
20.0000 degrees  Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:  Plain second end  Hub Diameter:  1.0625 inches second end  Precision Classification:  Iso precision class 2
Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:  Plain second end  Hub Diameter:  1.0625 inches second end  Precision Classification:  Iso precision class 2  First Groove Width:
Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:  Plain second end  Hub Diameter:  1.0625 inches second end  Precision Classification:  Iso precision class 2  First Groove Width:  0.0715 inches first end
Distance Between Body Face And Protruding Hub End:  1.0780 inches first end  Face Width:  0.188 inches  Bore Diameter:  0.6247 inches both ends  Hub Style Designator:  Plain second end  Hub Diameter:  1.0625 inches second end  Precision Classification: Iso precision class 2  First Groove Width:  0.0715 inches first end  First Groove Diameter:

## NSN 3020-00-330-0512

Spur Gear - Page 2 of 2

No Fiig: A27300



## Bolt Hole Circle Diameter: 1.750 inches axially through body, first end Material: Steel comp 416 Material Specification: Fed standard 66 assn standard single material response Surface Treatment: Passivate Style Designator: Protruding hubs Shelf Life: N/a Unit Of Measure: -- Demilitarization: