NSN 3020-00-334-7278

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-334-7278

De de Otele
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.3720 inches and 0.3730 inches
Teeth Quantity:
24
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
2 plain transversely through hub, first end
Outside Diameter:
0.404 inches
Nominallength:
0.171 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.106 inches first end
Face Width:
0.066 inches
Bore Diameter:
0.118 inches both ends
Hub Style Designator:
1 groove first end
Hub Diameter:
0.250 inches first end
First Groove Width:
0.040 inches first end
First Groove Diameter:
0.240 inches first end
Distance From End To First Groove:
0.029 inches first end
Mounting Hole Diameter:
0.043 inches transversely through hub, first end
Special Features:
Mounting holes located 0.049 in. From hub end 180 degrees apart
Material:

Aluminum alloy 2024

NSN 3020-00-334-7278

Spur Gear - Page 2 of 2

Fiig: A27300



Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No