NSN 3020-00-341-9845

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-341-9845 **Pitch Diameter:** Between 0.6289 inches and 0.6299 inches **Teeth Quantity:** 80 **Outside Diameter:** 0.644 inches Nominallength: 0.536 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.097 inches second end **Hub Style Designator:** 3 steps both ends **End Length:** 0.097 inches second end **Precision Classification:** Quality number 10 or quality number 11 **End Diameter:** 0.046 inches second end First Step Length: 0.046 inches first end First Step Diameter: 0.095 inches first end Second Step Length: 0.154 inches first end **Second Step Diameter:** 0.416 inches first end **Special Features:** Additional gear is third step of first end pitch diameter 0.4005 inch, 0.4015 inch, 51 teeth, 20 degree pressure angle Material: Steel comp 416 **Material Specification:** Qq-s-763, class 6, type c federal specification single material response **Style Designator:** Peripheral face, hubless Shelf Life:

--

N/a

Unit Of Measure:

NSN 3020-00-341-9845

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300