NSN 3020-00-347-4896

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-347-4896 **Body Style:** Plain, solid **Spline Quantity:** 10 both ends Pitch Diameter: 0.5937 inches **Teeth Quantity:** 19 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 0.2083 inches both ends **Backlash Designation:** Grade c **Hardness Rating:** 89.0 rockwell superficial 15-n and 91.0 rockwell superficial 15-n **Outside Diameter:** 0.656 inches Nominallength: 0.281 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.094 inches first end **Face Width:** 0.187 inches **Bore Diameter:** 0.201 inches both ends **Hub Style Designator:** Plain first end

Hub Diameter:

0.328 inches first end

Precision Classification:

Quality number 10 or quality number 11

Material:

Steel comp 4620

Material Specification:

Mil-s-7493, comp 4620 military specification single material response

Surface Treatment:

Passivate

NSN 3020-00-347-4896

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization: No

Mil-std (military Standard):

Mil-s-7493 spec.