NSN 3020-00-348-4562

Spur Gear - Page 1 of 2

Webbed, offset, with lightening holes

Body Style:

Pitch Diameter:



View Online at https://aerobasegroup.com/nsn/3020-00-348-4562

| 7.7500 inches |
|--|
| Teeth Quantity: |
| 62 |
| Bore Style: |
| W/ keyway both ends |
| Hardness Rating: |
| 82.4 rockwell b and 96.4 rockwell b |
| Outside Diameter: |
| 7.7997 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.8130 inches first end |
| Distance Between Body Face And Recessed Hub End: |
| 0.3750 inches second end |
| Face Width: |
| 1.000 inches |
| Bore Diameter: |
| 1.2502 inches both ends |
| Keyway Width: |
| 0.2435 inches both ends |
| Distance From Bore Center To Keyway Bottom: |
| 0.7420 inches both ends |
| Hub Style Designator: |
| Plain second end |
| Hub Diameter: |
| 2.180 inches second end |
| End Length: |
| 0.0630 inches first end |
| End Diameter: |
| 2.1800 inches second end |
| First Step Length: |
| 0.1880 inches first end |
| First Step Diameter: |
| 1.7500 inches first end |
| Second Step Length: |
| 0.562 inches first end |

NSN 3020-00-348-4562 Spur Gear - Page 2 of 2



| Second Step Diameter: |
|--------------------------------------|
| 2.1800 inches first end |
| Material: |
| Steel |
| Style Designator: |
| One protruding hub, one recessed hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A27300