NSN 3020-00-350-4353

Sprocket Wheel - Page 1 of 2

Between 15.734 inches and 15.734 inches

Counterbore Diameter:



View Online at https://aerobasegroup.com/nsn/3020-00-350-4353

Counterbore Depth:
Between 0.563 inches and 0.578 inches
Outside Diameter:
Between 27.1562 inches and 27.281 inches
Bolt Circle Diameter:
14.500 inches
Bore Diameter:
Between 13.062 inches and 13.188 inches
Bore Length:
Between 1.250 inches and 1.313 inches
Drilled Hole Diameter:
0.515 inches
Pitch Diameter:
25.038 inches
Securing Hole Quantity:
13
Face Width:
Between 1.250 inches and 1.3125 inches
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
55.0 rockwell c body and 60.0 rockwell c body
Counterbore Feature:
Included
Counterbore Location:
Aa end
Hole Location:
Located between teeth
Keying Facility:
Not included
Securing Method:
Drilled hole
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Block chain
Teeth Row Quantity:

NSN 3020-00-350-4353 Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
13
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 55.0 rockwell c and 60.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
6.590 inches
Material:
Steel, qq-s-626, comp fs1345 and steel, qq-s-626, fs9445
Material:
Steel, qq-s-626, comp fs1345 and steel, qq-s-626, fs9445
Surface Treatment:
Enamel
Style Designator:
Plain
Surface Treatment:
Enameled
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c