## NSN 3020-00-350-9012

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-350-9012

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.2500 inches **Teeth Quantity:** 60 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.164 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 1.2907 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.3750 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.2505 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.625 inches first end **Precision Classification:** Quality number 9 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize **Surface Treatment Specification:** 

Mil-a-8625, type 2 military specification single treatment response

## NSN 3020-00-350-9012

Spur Gear - Page 2 of 2

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.

