

View Online at <https://aerobasegroup.com/nsn/3020-00-354-1839>

**Groove Depth:**

0.5937 inches

**Groove Width:**

0.750 inches

**Outside Diameter:**

5.250 inches

**Overall Length:**

2.375 inches

**Keyway Width:**

Between 0.251 inches and 0.252 inches

**Thread Size:**

3/8-16

**Bore Diameter:**

Between 1.124 inches and 1.125 inches

**Bore Length:**

2.375 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 0.6805 inches and 0.6860 inches

**Drilled Hole Diameter:**

Between 0.2656 inches and 0.2812 inches

**V Groove Angle In Deg:**

38.0

**Pitch Diameter:**

Between 4.0625 inches and 5.250 inches

**Securing Hole Quantity:**

2

**Material And Location:**

Iron, cast

**Face Width:**

0.9375 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

1

**Counterbore Feature:**

Not included

**Hole Location:**

Located through body of pulley parallel to bore on 2.9375 in. Diameter boltcircle, one located through bottom of groove, one located 90 degrees from keyway and in line w/o 2812 in. Holes

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole and drilled hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Not offset

**Lightening Hole:**

Included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

2.1875 inches aa end and 1.625 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

1.3125 inches aa end and 0.125 inches bb end

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a