NSN 3020-00-354-3774

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-354-3774

| Outside Diameter: |
|---|
| Between 2.840 inches and 2.844 inches |
| Overall Length: |
| Between 1.656 inches and 1.661 inches |
| Keyway Width: |
| Between 0.189 inches and 0.190 inches |
| Bore Diameter: |
| Between 1.250 inches and 1.251 inches |
| Bore Length: |
| Between 1.656 inches and 1.661 inches |
| Distance From Center Of Bore To Bottom Of Keyway: |
| Between 0.724 inches and 0.729 inches |
| Pitch Diameter: |
| 2.879 inches |
| Face Width: |
| Between 0.641 inches and 0.647 inches |
| Guide: |
| Not included |
| Design Form: |
| Plain |
| Bore Type: |
| Straight |
| Metallic Hardness Rating And Location: |
| 50.0 rockwell c body |
| Counterbore Feature: |
| Not included |
| Keying Facility: |
| Included |
| Keying Facility Type: |
| Keyway |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Plain |
| Belt/chain/film Size For Which Designed: |
| Silent chain |
| Teeth Row Quantity: |
| 1 |
| Teeth Quantity Per Row: |
| 18 |
| Hardness Rating Test Method: |

Rockwell

NSN 3020-00-354-3774 Sprocket Wheel - Page 2 of 2



| Teeth Hardware Detings |
|---|
| Teeth Hardness Rating: |
| 50.0 rockwell c |
| Bore Bearing: |
| Not included |
| Hub External Keyway: |
| Not included |
| Tooth Pitch: |
| 0.500 inches |
| Hub End Outside Diameter And Location: |
| 2.000 inches both ends |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.730 inches aa end and 0.735 inches aa end |
| Material: |
| Steel |
| Material: |
| Steel |
| Quantity: |
| 1 |
| Style Designator: |
| Plain |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Т353-с |