## NSN 3020-00-354-3774

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-354-3774

Outside Diameter:
Between 2.840 inches and 2.844 inches
Overall Length:
Between 1.656 inches and 1.661 inches
Keyway Width:
Between 0.189 inches and 0.190 inches
Bore Diameter:
Between 1.250 inches and 1.251 inches
Bore Length:
Between 1.656 inches and 1.661 inches
Distance From Center Of Bore To Bottom Of Keyway:
Between 0.724 inches and 0.729 inches
Pitch Diameter:
2.879 inches
Face Width:
Between 0.641 inches and 0.647 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
50.0 rockwell c body
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Belt/chain/film Size For Which Designed:
Silent chain
Teeth Row Quantity:
1
Teeth Quantity Per Row:
18
Hardness Rating Test Method:

Rockwell

## **NSN 3020-00-354-3774** Sprocket Wheel - Page 2 of 2



Teeth Hardware Detings
Teeth Hardness Rating:
50.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
<b>Hub End Outside Diameter And Location:</b>
2.000 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.730 inches aa end and 0.735 inches aa end
Material:
Steel
Material:
Steel
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с