## NSN 3020-00-356-2013

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-356-2013

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
2.8750 inches
Teeth Quantity:
230
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Uns axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
96 axially through hub, first end
Mounting Hole Thread Size:
0.047 inches axially through hub, first end
Mounting Hole Type And Quantity:
4 threaded axially through hub, first end
Outside Diameter:
2.9000 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.7390 inches first end
Face Width:
0.100 inches
Bore Diameter:
1.9778 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.715 inches first end
End Diameter:
2.175 inches first end
First Step Length:
0.024 inches first end
First Step Diameter:
First Step Diameter: 2.275 inches first end
•
2.275 inches first end

## NSN 3020-00-356-2013

Spur Gear - Page 2 of 2



**Special Features:** 

Mtg holes spaced 90.0 degrees apart

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300