NSN 3020-00-358-5768

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-358-5768

Body Style:

Plain, solid

Attachment Method:

Mounting hole

Teeth Quantity:

Pitch Diameter:

57

Bore Style:

Plain both ends

Mounting Hole Thread Series Designator:

Between 0.5922 inches and 0.5937 inches

Unc transversely through hub, first end

Mounting Hole Thready Qty Per Inch (tpi):

56 transversely through hub, first end

Mounting Hole Thread Size:

0.086 inches transversely through hub, first end

Mounting Hole Type And Quantity:

1 threaded transversely through hub, first end

Outside Diameter:

0.613 inches

Nominallength:

0.188 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.108 inches first end

Face Width:

0.080 inches

Bore Diameter:

0.125 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.310 inches first end

Precision Classification:

Quality number 9

Material:

Copper alloy 510 or copper alloy 524 or copper alloy 544

Material Specification:

Qq-b750 federal specification single material response

NSN 3020-00-358-5768

Spur Gear - Page 2 of 2



•		
StVID	l Jacian	ator.
OLYIC	Design	atoi.

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300