NSN 3020-00-358-5809



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-358-5809 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.8750 inches **Teeth Quantity:** 230 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Uns axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 96 axially through hub, first end **Mounting Hole Thread Size:** 0.047 inches axially through hub, first end **Mounting Hole Type And Quantity:** 4 threaded axially through hub, first end **Outside Diameter:** 2.900 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.399 inches first end **Face Width:** 0.100 inches **Bore Diameter:** 2.378 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.375 inches first end **End Diameter:** 2.575 inches first end First Step Length: 0.024 inches first end

Bolt Hole Circle Diameter: 2.475 inches axially through hub, first end

First Step Diameter: 2.675 inches first end

NSN 3020-00-358-5809

Spur Gear - Page 2 of 2

Fiig: A27300



Special Features:
Mtg holes spaced 90 degrees apart
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, t6 federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli