## NSN 3020-00-360-7172

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-360-7172

Body Style:						
Plain, solid						
Pitch Diameter:						
5.8290 inches						
Teeth Quantity:						
60						
Bore Style:						
W/ keyway both ends						
Hardness Rating:						
180.0 brinell standard and 240.0 brinell standard						
Outside Diameter:						
5.9850 inches						
Teeth Type:						
Single helix						
Tooth Form:						
Standard						
Tooth Direction:						
Right						
Pressure Angle:						
14.5000 degrees						
Helix Angle:						
31.0000 degrees						
Distance Between Body Face And Protruding Hub End:						
Distance Between Body Face And Protruding Hub End:						
Distance Between Body Face And Protruding Hub End: 0.125 inches first end						
0.125 inches first end						
0.125 inches first end  Face Width:						
0.125 inches first end  Face Width:  0.813 inches						
0.125 inches first end  Face Width:  0.813 inches  Bore Diameter:						
0.125 inches first end  Face Width: 0.813 inches  Bore Diameter: 1.2505 inches both ends						
0.125 inches first end  Face Width:  0.813 inches  Bore Diameter:  1.2505 inches both ends  Keyway Width:						
0.125 inches first end  Face Width:  0.813 inches  Bore Diameter:  1.2505 inches both ends  Keyway Width:  0.3125 inches both ends						
0.125 inches first end  Face Width: 0.813 inches  Bore Diameter: 1.2505 inches both ends  Keyway Width: 0.3125 inches both ends  Distance From Bore Center To Keyway Bottom:						
0.125 inches first end  Face Width:  0.813 inches  Bore Diameter:  1.2505 inches both ends  Keyway Width:  0.3125 inches both ends  Distance From Bore Center To Keyway Bottom:  0.7328 inches both ends						
0.125 inches first end  Face Width: 0.813 inches  Bore Diameter: 1.2505 inches both ends  Keyway Width: 0.3125 inches both ends  Distance From Bore Center To Keyway Bottom: 0.7328 inches both ends  Hub Style Designator:						
0.125 inches first end  Face Width:  0.813 inches  Bore Diameter:  1.2505 inches both ends  Keyway Width:  0.3125 inches both ends  Distance From Bore Center To Keyway Bottom:  0.7328 inches both ends  Hub Style Designator:  Plain both ends						
0.125 inches first end  Face Width: 0.813 inches  Bore Diameter: 1.2505 inches both ends  Keyway Width: 0.3125 inches both ends  Distance From Bore Center To Keyway Bottom: 0.7328 inches both ends  Hub Style Designator:  Plain both ends  Hub Diameter:						
0.125 inches first end  Face Width: 0.813 inches  Bore Diameter: 1.2505 inches both ends  Keyway Width: 0.3125 inches both ends  Distance From Bore Center To Keyway Bottom: 0.7328 inches both ends  Hub Style Designator:  Plain both ends  Hub Diameter: 1.875 inches second end						
0.125 inches first end  Face Width: 0.813 inches  Bore Diameter: 1.2505 inches both ends  Keyway Width: 0.3125 inches both ends  Distance From Bore Center To Keyway Bottom: 0.7328 inches both ends  Hub Style Designator:  Plain both ends  Hub Diameter: 1.875 inches second end  Material:						
0.125 inches first end  Face Width: 0.813 inches  Bore Diameter: 1.2505 inches both ends  Keyway Width: 0.3125 inches both ends  Distance From Bore Center To Keyway Bottom: 0.7328 inches both ends  Hub Style Designator: Plain both ends  Hub Diameter: 1.875 inches second end  Material:  Steel						
0.125 inches first end  Face Width: 0.813 inches  Bore Diameter: 1.2505 inches both ends  Keyway Width: 0.3125 inches both ends  Distance From Bore Center To Keyway Bottom: 0.7328 inches both ends  Hub Style Designator:  Plain both ends  Hub Diameter: 1.875 inches second end  Material:  Steel  Style Designator:						

## NSN 3020-00-360-7172

Helical Gear - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A27300