## NSN 3020-00-366-8037

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-366-8037	_
Attachment Method:	
Clamp	
Pitch Diameter:	
0.6250 inches	
Teeth Quantity:	
60	
Bore Style:	
Plain both ends	
Outside Diameter:	
0.645 inches	
Tooth Form:	
Standard	
Pressure Angle:	
20.0000 degrees	
Distance Between Body Face And Protruding Hub End:	
0.062 inches second end	
Face Width:	
0.104 inches	
Bore Diameter:	
0.120 inches both ends	
Hub Style Designator:	
Split first end	
Hub Diameter:	
0.185 inches both ends	
Clamping Surface Length:	
0.172 inches first end	
Precision Classification:	
Quality number 10	
Material:	
Steel comp 303	
Material Specification:	
Qq-s-764, type 303, cond a federal specification single material response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Mil-std-171, finish no. 5.4.1 military specification single treatment response	
Style Designator:	
Protruding hubs	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 3020-00-366-8037

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.