## NSN 3020-00-366-8044

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-366-8044

Attachment Method:				
Clamp				
Pitch Diameter:				
0.6250 inches				
Teeth Quantity:				
60				
Bore Style:				
Plain both ends				
Outside Diameter:				
0.548 inches				
Nominallength:				
0.395 inches				
Tooth Form:				
Standard				
Pressure Angle:				
20.0000 degrees				
Distance Between Body Face And Protruding Hub End:				
0.062 inches second end				
Face Width:				
0.104 inches				
Bore Diameter:				
0.125 inches both ends				
Hub Style Designator:				
Split first end				
Hub Diameter:				
0.185 inches first end				
Clamping Surface Length:				
0.172 inches first end				
Precision Classification:				
Quality number 10				
Material:				
Steel comp 303				
Material Specification:				
Qq-s-764, type 303, cond a federal specification single material response				
Surface Treatment:				
Passivate				
Surface Treatment Specification:				
Mil-std-171, finish no. 5.4.1 military specification single treatment response				
Style Designator:				
Protruding hubs				
Shelf Life:				
N/a				

## NSN 3020-00-366-8044

Spur Antibacklash Gear - Page 2 of 2



ι	Jnit	Of	Measure:
•	,,,,,	•	moudai c.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.