NSN 3020-00-368-8237

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-368-8237 **Attachment Method:** Clamp Pitch Diameter: 0.7500 inches **Teeth Quantity:** 72 **Bore Style:** Plain both ends **Outside Diameter:** 0.771 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.050 inches second end **Face Width:** 0.104 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.312 inches second end **Clamping Surface Length:** 0.172 inches first end **Precision Classification:** Quality number 10 First Groove Width: 0.029 inches second end **First Groove Diameter:** 0.290 inches second end **Distance From End To First Groove:** 0.021 inches second end Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303, cond a federal specification single material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Mil-std-171, finish no. 5.4.1 military specification single treatment response

NSN 3020-00-368-8237

Spur Antibacklash Gear - Page 2 of 2



Style Designator:
Protruding hubs
Furnished Items And Quantity:
1 retaining ring and 1 stop pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-std-171 spec.