NSN 3020-00-373-1761



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-373-1761 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.7000 inches **Teeth Quantity:** 56 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.725 inches Nominallength: 0.202 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.140 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:**

1 step first end
End Length:
0.015 inches first end
Precision Classification:
Quality number 9
End Diameter:
0.250 inches first end
First Step Length:
0.125 inches first end

NSN 3020-00-373-1761

Spur Gear - Page 2 of 2

A27300



First Step Diameter:
0.375 inches first end
Material:
Steel comp 416
Material Specification:
Qq-s-764, type 416 cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Cmc 197-117, canadian marconi co mfr ref single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: