NSN 3020-00-373-1761

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-373-1761

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.7000 inches **Teeth Quantity:** 56 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 0.725 inches Nominallength: 0.202 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.140 inches first end Face Width: 0.062 inches **Bore Diameter:** 0.187 inches both ends Hub Style Designator: 1 step first end End Length: 0.015 inches first end **Precision Classification:** Quality number 9 End Diameter: 0.250 inches first end First Step Length: 0.125 inches first end

NSN 3020-00-373-1761

Spur Gear - Page 2 of 2



First Step Diameter:

0.375 inches first end

Material:

Steel comp 416

Material Specification:

Qq-s-764, type 416 cond a federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Cmc 197-117, canadian marconi co mfr ref single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A27300