NSN 3020-00-376-4229



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-376-4229 **Outside Diameter:** 7.718 inches **Overall Length:** 1.813 inches **Keyway Width:** 0.375 inches **Thread Size:** 2-3/8 in.-16 **Bore Diameter:** 1.250 inches Bore Length: 1.813 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.8125 inches Pitch Diameter: 7.6806 inches **Securing Hole Quantity:** 2 **Furnished Items And Quantity:** Setscrews, 2 Face Width: 0.344 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** Located 90 degrees from keyway, located on top of keyway **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Threaded hole

Lightening Hole:

Protruding Hub Characteristic:

Not included

Plain

NSN 3020-00-376-4229 Sprocket Wheel - Page 2 of 2



Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
37
Asa Standard Chain Number:
50
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.625 inches
Hub End Outside Diameter And Location:
2.000 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
1.031 inches aa end and 0.438 inches bb end
Material:
Steel, cast
Material:
Steel
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
T353-c