## NSN 3020-00-378-6406

Spur Gear - Page 1 of 2



)6

| View Online at https://aerobasegroup.com/nsn/3020-00-378-640 |
|--|
| Body Style:  |
| Webbed, offset, with lightening holes                        |
| Attachment Method:   |
| Mounting hole  |
| Pitch Diameter:  |
| Between 3.5000 inches and 3.5005 inches                      |
| Teeth Quantity:  |
| 84   |
| Bore Style:  |
| W/counterbore both ends                                      |
| Backlash Designation:  |
| Grade e  |
| Mounting Hole Thread Series Designator:                      |
| Unc axially through body, first end                          |
| Mounting Hole Thready Qty Per Inch (tpi):                    |
| 40 axially through body, first end                           |
| Mounting Hole Type And Quantity:                             |
| 3 threaded axially through body, first end                   |
| Nominallength:   |
| 0.593 inches   |
| Tooth Form:  |
| Standard   |
| Pressure Angle:  |
| 14.5000 degrees  |
| Distance Between Body Face And Protruding Hub End:           |
| 0.250 inches first end                                       |
| Face Width:  |
| 0.125 inches   |
| Bore Diameter:   |
| 1.000 inches both ends                                       |
| Counterbore Depth:   |
| 0.250 inches both ends                                       |
| Hub Diameter:  |
| 1.375 inches second end                                      |
| End Length:  |
| 0.250 inches first end                                       |
| Bolt Hole Circle Diameter:                                   |
| 3.093 inches axially through body, first end                 |
| Style Designator:  |
| Protruding hubs  |
| Shalf Life:  |

N/a

## NSN 3020-00-378-6406

Spur Gear - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A27300