NSN 3020-00-379-6307

0.500 inches first endFirst Step Length:0.094 inches first end



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-379-6307 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.5000 inches **Teeth Quantity:** 120 **Bore Style:** W/counterbore both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Mounting Hole Thread Size:** 0.112 inches axially through body, first end **Mounting Hole Type And Quantity:** 3 plain axially through body, first end and 3 threaded axially through body, first end **Outside Diameter:** 2.541 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.156 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.2037 inches both ends **Counterbore Depth:** 0.0620 inches second end **Counterbore Diameter:** 1.3753 inches second end **Hub Style Designator:** 1 step first end **End Length:** 0.0625 inches first end **Precision Classification:** Quality number 12 **End Diameter:**

NSN 3020-00-379-6307

Spur Gear - Page 2 of 2

Fiig: A27300



First Step Diameter:
1.625 inches first end
Mounting Hole Diameter:
0.147 inches axially through body, first end
Material:
Steel comp 416
Material Specification:
Fed standard 66 federal standard single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No