## NSN 3020-00-391-2822

Sprocket Wheel - Page 1 of 2



Oproduct Whiter Tage Tot 2	arvup
View Online at https://aerobasegroup.com/nsn/3020-00-391-2822	
Spline Major Diameter:	
Between 3.250 inches and 3.280 inches	
Counterbore Diameter:	
Between 3.280 inches and 3.283 inches	
Counterbore Depth:	
1.016 inches	
Outside Diameter:	
8.070 inches	
Overall Length:	
Between 3.180 inches and 3.188 inches	
Spline Quantity:	
6	
Spline Minor Diameter:	
Between 2.762 inches and 2.765 inches	
Pitch Diameter:	
Between 7.036 inches and 7.099 inches	
Face Width:	
Between 2.555 inches and 3.805 inches	
Guide:	
Not included	
Design Form:	
Plain	
Bore Type:	
Straight spline	
Metallic Hardness Rating And Location:	
15.2 rockwell c body and 22.0 rockwell c body	
Spline Length:	
Between 2.164 inches and 2.172 inches	
Counterbore Feature:	
Included	
Counterbore Location:	
Aa end	
Lightening Hole:	
Not included	
Protruding Hub Characteristic:	

Stepped

**Groove/step Location:** 

Both ends

Belt/chain/film Size For Which Designed:

**Roller Chain Pitch Type For Which Designed:** 

Single pitch

## **NSN 3020-00-391-2822** Sprocket Wheel - Page 2 of 2



Teeth Row Quantity:
1
Teeth Quantity Per Row:
11
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 15.2 rockwell c and 22.8 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
2.000 inches
First Step Face Largest Diameter And Location:
4.080 inches both ends and 4.090 inches both ends
First Step Length And Location:
0.406 inches both ends
Hub End Outside Diameter And Location:
3.990 inches aa end and 4.000 inches aa end and 4.438 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
1.141 inches both ends and 1.172 inches both ends
Material:
Steel, fed standard no. 66, aisi c1040 or sae 1040
Material:
Steel, fed standard no. 66, aisi c1040 or sae 1040
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c