

View Online at <https://aerobasegroup.com/nsn/3020-00-392-4693>

Groove Depth:

Between 0.780 inches and 0.873 inches

Groove Width:

Between 0.812 inches and 1.000 inches

Outside Diameter:

7.500 inches

Overall Length:

3.562 inches

Bolt Circle Diameter:

3.500 inches

Keyway Width:

Between 0.376 inches and 0.381 inches

Thread Size:

3/8-16

Bore Diameter:

Between 2.000 inches and 2.001 inches

Bore Length:

3.406 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 1.176 inches and 1.186 inches

V Groove Angle In Deg:

38.0

Securing Hole Quantity:

2

Material And Location:

Iron, cast

Face Width:

2.656 inches

Design Form:

Spoked

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

On end of hub parallel to bore, 180.0 degrees apart

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Bb end

Hub End Outside Diameter And Location:

2.875 inches aa end and 3.000 inches bb end

First Step Face Largest Diameter And Location:

3.000 inches aa end

First Step Length And Location:

0.750 inches aa end

Hub End Outside Diameter And Location:

2.875 inches aa end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-a