NSN 3020-00-395-1353

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-395-1353

| Body Style: |
|--|
| Webbed, offset, solid |
| Pitch Diameter: |
| 1.6666 inches |
| Teeth Quantity: |
| 40 |
| Bore Style: |
| W/ keyway both ends |
| Hardness Rating: |
| 43.0 rockwell c and 47.0 rockwell c |
| Outside Diameter: |
| 1.746 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.200 inches first end |
| Face Width: |
| 0.260 inches |
| Bore Diameter: |
| 0.313 inches both ends |
| Keyway Width: |
| 0.064 inches both ends |
| Distance From Bore Center To Keyway Bottom: |
| 0.184 inches both ends |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 0.620 inches both ends |
| Precision Classification: |
| Quality number 8 |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Mil-s-6049 military specification single material response |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 3020-00-395-1353

Spur Gear - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-s-6049 spec.