NSN 3020-00-402-2513

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-402-2513 **Attachment Method:** Mounting hole **Pitch Diameter:** Between 1.4990 inches and 1.5000 inches **Teeth Quantity:** 72 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.540 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 1.125 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.375 inches first end **Special Features:** Thd attaching holes located 90 degrees apart through hub Material: Steel comp 303 hub **Material Specification:** Qq-s-764, cond a federal specification single material response hub **Surface Treatment:**

Passivate hub **Style Designator:** Protruding hub Shelf Life: N/a

NSN 3020-00-402-2513

Spur Antibacklash Gear - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A27300