NSN 3020-00-402-2968

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-402-2968

Body Style:

Webbed, offset, solid

Attachment Method:

Mounting hole

Pitch Diameter:

Between 0.9993 inches and 1.0000 inches

Teeth Quantity:

72

Bore Style:

Plain both ends

Mounting Hole Thread Series Designator:

Unc axially through body, first end

Mounting Hole Thready Qty Per Inch (tpi):

56 axially through body, first end

Mounting Hole Thread Size:

0.086 inches axially through body, first end

Mounting Hole Type And Quantity:

3 threaded axially through body, first end

Outside Diameter:

1.027 inches

Nominallength:

0.192 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.015 inches first end

Body Recess Depth:

0.067 inches second end

Face Width:

0.177 inches

Bore Diameter:

0.187 inches both ends

Hub Style Designator:

Plain first end

Hub Diameter:

0.687 inches first end

Bolt Hole Circle Diameter:

0.400 inches axially through body, first end

Material:

Steel comp 630

NSN 3020-00-402-2968

Spur Gear - Page 2 of 2



Material Specification:

Ams 5643, 17-4ph assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300