NSN 3020-00-402-2968

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-402-2968

Body Style:	
Webbed, offset, solid	
Attachment Method:	
Mounting hole	
Pitch Diameter:	
Between 0.9993 inches and 1.0000 inches	
Teeth Quantity:	
72	
Bore Style:	
Plain both ends	
Mounting Hole Thread Series Designator:	
Unc axially through body, first end	
Mounting Hole Thready Qty Per Inch (tpi):	
56 axially through body, first end	
Mounting Hole Thread Size:	
0.086 inches axially through body, first end	
Mounting Hole Type And Quantity:	
3 threaded axially through body, first end	
Outside Diameter:	
1.027 inches	
Nominallength:	
0.192 inches	
Tooth Form:	
Standard	
Pressure Angle:	
20.0000 degrees	
Distance Between Body Face And Protruding Hub End:	
0.015 inches first end	
Body Recess Depth:	
0.067 inches second end	
Face Width:	
0.177 inches	
Bore Diameter:	
0.187 inches both ends	
Hub Style Designator:	
Plain first end	
Hub Diameter:	
0.687 inches first end	
Bolt Hole Circle Diameter:	
0.400 inches axially through body, first end	
Material:	
Ctaal samp 620	

Steel comp 630

NSN 3020-00-402-2968

Spur Gear - Page 2 of 2



Material Specification:
Ams 5643, 17-4ph assn standard single material response
Surface Treatment:
Passivate

Style Designator:Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300