NSN 3020-00-405-4234

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-405-4234

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 4.3125 inches **Teeth Quantity:** 276 **Bore Style:** W/counterbore both ends Mounting Hole Thread Series Designator: Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 axially through hub, first end Mounting Hole Thread Size: 0.112 inches axially through hub, first end Mounting Hole Type And Quantity: 4 threaded axially through hub, first end **Outside Diameter:** 4.342 inches Nominallength: 0.250 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.125 inches first end Face Width: 0.125 inches **Bore Diameter:** 3.355 inches both ends **Counterbore Depth:** 0.125 inches first end **Counterbore Diameter:** 3.429 inches first end Hub Style Designator: 1 step first end End Length: 0.064 inches first end **Precision Classification:** Quality number 10 or quality number 11

NSN 3020-00-405-4234

Spur Gear - Page 2 of 2

A27300



End Diameter: 3.622 inches first end First Step Length: 0.061 inches first end First Step Diameter: 4.152 inches first end **Bolt Hole Circle Diameter:** 3.844 inches axially through hub, first end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Style Designator: Protruding hub Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: