NSN 3020-00-406-3515

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-406-3515 **Attachment Method:** Clamp Pitch Diameter: 1.9375 inches **Teeth Quantity:** 124 **Bore Style:** Plain both ends **Backlash Designation:** Grade d **Outside Diameter:** 1.969 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.264 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.187 inches both ends **Precision Classification:** Quality number 12 **Special Features:** 1st end hub has 2-56 unc-2a by 0.250 in. Lg screw hole Material: Aluminum alloy 2024 **Material Specification:** Qq-a-268 temper t4 or t6 federal specification single material response **Surface Treatment:** Cadmium spring **Surface Treatment Specification:** Qq-p-416, cl 2, type 11 federal specification single treatment response spring **Style Designator:** Protruding hubs Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 3020-00-406-3515

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.