## NSN 3020-00-406-3519

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-406-3519

#### **Pitch Diameter:**

1.5625 inches

**Teeth Quantity:** 

100

## Bore Style:

Plain both ends

## Backlash Designation:

Grade d

## **Outside Diameter:**

1.5937 inches

#### **Tooth Form:**

Standard

#### **Pressure Angle:**

20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.250 inches first end

#### Face Width:

0.125 inches

#### Bore Diameter:

0.250 inches both ends

## Hub Style Designator:

Pinned first end

## Hub Diameter:

0.375 inches first end

## **Precision Classification:**

Quality number 12

#### Material:

Steel comp 303 hub

## Material Specification:

Qq-a-250/4, t4 federal specification single material response clamp

#### Surface Treatment:

Passivate hub

## Surface Treatment Specification:

Mil-f-14072 military specification single treatment response hub

#### Style Designator:

Protruding hub

Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

No

# NSN 3020-00-406-3519

Spur Antibacklash Gear - Page 2 of 2

Fiig: A27300 Mil-std (military Standard):

Mil-s-7720 spec.

