# NSN 3020-00-406-3537

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-406-3537

## **Body Style:**

Plain, solid

### **Attachment Method:**

Clamp

# Pitch Diameter:

1.9375 inches

## **Teeth Quantity:**

124

### Bore Style:

Plain both ends

### **Backlash Designation:**

Grade d

#### Outside Diameter:

1.958 inches

#### **Tooth Form:**

Standard

# Pressure Angle:

20.0000 degrees

## Distance Between Body Face And Protruding Hub End:

0.234 inches first end

## Face Width:

0.125 inches

## Bore Diameter:

0.250 inches both ends

### **Precision Classification:**

Quality number 12

### Material:

Steel comp 303

### **Material Specification:**

Qq-s-763, class 303, cond a federal specification single material response

#### Surface Treatment:

Passivate

### Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

#### Style Designator:

Protruding hub

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

# NSN 3020-00-406-3537

Spur Gear - Page 2 of 2

Fiig: A27300 Mil-std (military Standard): Mil-f-14072 spec.

