

View Online at <https://aerobasegroup.com/nsn/3020-00-406-4583>

Groove Depth:

Between 0.350 inches and 0.613 inches

Groove Width:

Between 0.313 inches and 0.438 inches

Outside Diameter:

Between 7.548 inches and 7.576 inches

Keyway Width:

Between 0.2510 inches and 0.2530 inches

Bore Diameter:

Between 1.000 inches and 1.002 inches

Bore Length:

Between 1.840 inches and 1.910 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.611 inches

V Groove Angle In Deg:

40.0

Pitch Diameter:

Between 7.548 inches and 7.576 inches

Material And Location:

Iron, malleable

Face Width:

Between 3.265 inches and 3.327 inches

Design Form:

Spoked

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

4 or 2

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Key

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Both ends

Hub End Outside Diameter And Location:

1.750 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.720 inches both ends and 0.780 inches both ends

Quantity:

1

Surface Treatment:

Enamel

Style Designator:

Webbed or spoked

Surface Treatment:

Enameled

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a