## NSN 3020-00-407-1193

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-407-1193 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.1250 inches **Teeth Quantity:** 72 **Bore Style:** Plain both ends **Backlash Designation:** Grade d **Mounting Hole Thread Series Designator:** Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 axially through hub, first end **Mounting Hole Thread Size:** 0.086 inches axially through hub, first end **Mounting Hole Type And Quantity:** 1 threaded axially through hub, first end **Outside Diameter:** 1.156 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.234 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.241 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.500 inches first end

**Precision Classification:** Quality number 12 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response

## NSN 3020-00-407-1193

Spur Gear - Page 2 of 2



_	•		_	-		
<b>ن</b>	ırfa	$\sim$	I rc	nter	nor	٠.

Anodize

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300