## NSN 3020-00-407-1193

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-407-1193

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.1250 inches **Teeth Quantity:** 72 **Bore Style:** Plain both ends **Backlash Designation:** Grade d Mounting Hole Thread Series Designator: Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 axially through hub, first end Mounting Hole Thread Size: 0.086 inches axially through hub, first end Mounting Hole Type And Quantity: 1 threaded axially through hub, first end **Outside Diameter:** 1.156 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.234 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.241 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 12 Material: Aluminum alloy 2024

#### Material Specification:

Qq-a-225/6, t4 federal specification single material response

# NSN 3020-00-407-1193

Spur Gear - Page 2 of 2

Surface Treatment:

Anodize

Style Designator:

Protruding hub

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A27300

