NSN 3020-00-407-4808

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-407-4808 **Attachment Method:** Clamp Pitch Diameter: 0.8750 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Outside Diameter:** 0.894 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.308 inches first end **Face Width:** 0.124 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.248 inches first end **Clamping Surface Length:** 0.256 inches first end **Precision Classification:** Quality number 13 or quality number 14 Material: Aluminum alloy 2024 or aluminum alloy 6062 **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Protruding hub Shelf Life: **Unit Of Measure:**

N/a
Unit Of Measure:
-Demilitarization:

NSN 3020-00-407-4808

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.