## NSN 3020-00-407-6623

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-407-6623

Body Style: Plain, solid  Pitch Diameter: Between 0.6448 inches and 0.6458 inches  Teeth Quantity: 62  Bore Style: W/counterbore counter bore, second end  Backlash Designation: Grade c  Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end  Outside Diameter:
Pitch Diameter:  Between 0.6448 inches and 0.6458 inches  Teeth Quantity: 62  Bore Style:  W/counterbore counter bore, second end  Backlash Designation:  Grade c  Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end
Between 0.6448 inches and 0.6458 inches  Teeth Quantity: 62  Bore Style: W/counterbore counter bore, second end  Backlash Designation: Grade c  Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end
Teeth Quantity: 62 Bore Style: W/counterbore counter bore, second end Backlash Designation: Grade c Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end
Bore Style:  W/counterbore counter bore, second end  Backlash Designation:  Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end
Bore Style:  W/counterbore counter bore, second end  Backlash Designation:  Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end
W/counterbore counter bore, second end  Backlash Designation:  Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end
Backlash Designation: Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end
Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end
Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end
1 threaded transversely through hub, first end
•
Outside Diameter:
0.664 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.187 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.1880 inches counter bore, second end
Counterbore Depth:
0.1250 inches counter bore, second end
Counterbore Diameter:
0.225 inches counter bore, second end
Hub Style Designator:
Pinned first end
Hub Diameter:
0.370 inches first end
Precision Classification:
Quality number 10
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

## NSN 3020-00-407-6623

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
•

Mil-std (military Standard):

Mil-a-8625 spec.