## NSN 3020-00-407-6623

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-407-6623

| Body Style: Plain, solid  Pitch Diameter: Between 0.6448 inches and 0.6458 inches  Teeth Quantity: 62  Bore Style: W/counterbore counter bore, second end  Backlash Designation: Grade c  Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end  Outside Diameter: |
|--|
| Pitch Diameter:  Between 0.6448 inches and 0.6458 inches  Teeth Quantity: 62  Bore Style:  W/counterbore counter bore, second end  Backlash Designation:  Grade c  Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end   |
| Between 0.6448 inches and 0.6458 inches  Teeth Quantity: 62  Bore Style: W/counterbore counter bore, second end  Backlash Designation: Grade c  Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end  |
| Teeth Quantity: 62 Bore Style: W/counterbore counter bore, second end Backlash Designation: Grade c Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end  |
| Bore Style:  W/counterbore counter bore, second end  Backlash Designation:  Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end  |
| Bore Style:  W/counterbore counter bore, second end  Backlash Designation:  Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end  |
| W/counterbore counter bore, second end  Backlash Designation:  Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end   |
| Backlash Designation: Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end  |
| Grade c  Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end  |
| Mounting Hole Type And Quantity:  1 threaded transversely through hub, first end   |
| 1 threaded transversely through hub, first end   |
| •  |
| Outside Diameter:  |
|  |
| 0.664 inches   |
| Tooth Form:  |
| Standard   |
| Pressure Angle:  |
| 20.0000 degrees  |
| Distance Between Body Face And Protruding Hub End:   |
| 0.187 inches first end   |
| Face Width:  |
| 0.125 inches   |
| Bore Diameter:   |
| 0.1880 inches counter bore, second end   |
| Counterbore Depth:   |
| 0.1250 inches counter bore, second end   |
| Counterbore Diameter:  |
| 0.225 inches counter bore, second end  |
| Hub Style Designator:  |
| Pinned first end   |
| Hub Diameter:  |
| 0.370 inches first end   |
| Precision Classification:  |
| Quality number 10  |
| Material:  |
| Aluminum alloy 2024  |
| Material Specification:  |
| Qq-a-225/6, t4 federal specification single material response  |
| Surface Treatment:   |
| Anodize  |
| Surface Treatment Specification:   |

Mil-a-8625, type 1 military specification single treatment response

## NSN 3020-00-407-6623

Spur Gear - Page 2 of 2



| Style Designator: |
|-------------------|
| Protruding hub    |
| Shelf Life:       |
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |
| •                 |

Mil-std (military Standard):

Mil-a-8625 spec.