NSN 3020-00-409-8764

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-409-8764 **Pitch Diameter:** Between 1.7350 inches and 1.7360 inches **Teeth Quantity:** 125 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 1.763 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 10 Material: Stainless steel spring **Material Specification:** Qq-s-764 federal specification single material response hub **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Qq-p-35, type 2 federal specification single treatment response hub **Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 3020-00-409-8764

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.