# NSN 3020-00-410-5501

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-410-5501

# **Pitch Diameter:**

Between 2.2212 inches and 2.2222 inches

# **Teeth Quantity:**

160

# Bore Style:

Plain both ends

# **Outside Diameter:**

2.249 inches

## Tooth Form:

Standard

## **Pressure Angle:**

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

## 0.281 inches first end

Face Width:

## 0.104 inches

Bore Diameter:

# 0.250 inches both ends

Hub Style Designator:

Pinned first end

# Hub Diameter:

0.500 inches first end

# **Precision Classification:**

Quality number 10

## Material:

Steel comp 303 hub

# **Material Specification:**

Qq-a-225/6 federal specification single material response teeth

## **Surface Treatment:**

Passivate hub

# Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response teeth

## **Style Designator:**

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A27300

NSN 3020-00-410-5501

Spur Antibacklash Gear - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

