NSN 3020-00-410-5575

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-410-5575

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.8323 inches and 0.8333 inches
Teeth Quantity:
60
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Mounting Hole Thread Size:
0.138 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 countersunk transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
0.860 inches
Nominallength:
0.375 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.500 inches first end
Precision Classification:
Quality number 10
Mounting Hole Diameter:
0.086 inches transversely through hub, first end
Special Features

opeciai i catales.

Mtgholes 90 degs apart

NSN 3020-00-410-5575

Spur Gear - Page 2 of 2

Material:

A27300



Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Furnished Items And Quantity:
1 setscrew
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: