# NSN 3020-00-413-1772

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-413-1772

Body Style:
Plain, solid
Pitch Diameter:
0.7500 inches
Teeth Quantity:
36
Bore Style:
W/counterbore counterbore, first end
Backlash Designation:
Grade a
Features Provided:
Casehardened and integral key
Outside Diameter:
0.770 inches
Tooth Form:
Special
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.578 inches first end
Face Width:
0.175 inches
Bore Diameter:
0.126 inches counterbore, first end
Counterbore Depth:
0.708 inches counterbore, first end
Counterbore Diameter:
0.500 inches counterbore, first end
Hub Style Designator:
1 step second end
End Length:
0.540 inches first end
Precision Classification:
Quality number 9
End Diameter:
0.568 inches first end
First Step Length:
0.038 inches second end
First Step Diameter:
0.623 inches first end
Special Features:
With integral key in counterbore portion of first end

# NSN 3020-00-413-1772

Spur Gear - Page 2 of 2



Mate	

Steel comp 8620

## **Material Specification:**

Fed standard 66 federal standard single material response

## **Style Designator:**

Protruding hubs

#### **Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Shelf Life:

N/a

#### **Unit Of Measure:**

\_\_

#### **Demilitarization:**

Yes - demil/mli

#### Fiig:

A27300