NSN 3020-00-415-6522

Gear Cluster - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3020-00-415-6522

Attachment Method:
Mounting hole
Bore Style:
Plain both ends
Design Type:
Spur second gear
Construction:
Assembled
Outside Diameter:
0.664 inches second gear
Nominallength:
0.312 inches
Hub Length:
0.140 inches between first and second gear
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.500 inches between first and second gear
Precision Classification:
Quality number 10 all gears or quality number 12 all gears
Material:
Material:
Material: Steel comp 303 first gear
Material: Steel comp 303 first gear Material Specification:
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment:
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification:
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, finish no. 5.4.1 military specification single treatment response
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, finish no. 5.4.1 military specification single treatment response Shelf Life:
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, finish no. 5.4.1 military specification single treatment response Shelf Life: N/a
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, finish no. 5.4.1 military specification single treatment response Shelf Life: N/a
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, finish no. 5.4.1 military specification single treatment response Shelf Life: N/a Unit Of Measure:
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, finish no. 5.4.1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, finish no. 5.4.1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No
Material: Steel comp 303 first gear Material Specification: Qq-s-763, class 303, cond a federal specification single material response first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, finish no. 5.4.1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: