

View Online at <https://aerobasegroup.com/nsn/3020-00-419-0525>

Outside Diameter:

Between 5.360 inches and 5.365 inches

Outside Diameter:

5.625 inches

Keyway Width:

Between 0.312 inches and 0.315 inches

Bore Diameter:

Between 1.371 inches and 1.376 inches

Bore Length:

1.813 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.758 inches and 0.763 inches

Pitch Diameter:

5.411 inches

Face Width:

2.452 inches

Guide:

Included

Design Form:

Webbed

Bore Type:

Straight

Counterbore Feature:

Not included

Guide Type:

Sprocket side flange

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Split-tapered bushing

Lightening Hole:

Not included

Securing Location:

Bb end

Belt/chain/film Size For Which Designed:

Positive drive belt

Teeth Row Quantity:

1

Teeth Quantity Per Row:

34

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Tooth Pitch:

0.500 inches

Distance From Outside Flange/rim To Hub End And Location:

0.383 inches aa end

Material:

Steel, qq-s-631, 1010 through 1025 or qq-s-741 astm a36

Material:

Steel, qq-s-631, 1010 through 1025 or qq-s-741 astm a36

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-c