## NSN 3020-00-420-1215

Spur Antibacklash Gear - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3020-00-420-1215

| Attachment Method:  |
|---|
| Clamp   |
| Pitch Diameter:   |
| Between 1.4990 inches and 1.5000 inches                                       |
| Teeth Quantity:   |
| 144   |
| Bore Style:   |
| Plain both ends   |
| Outside Diameter:   |
| 1.521 inches  |
| Tooth Form:   |
| Stub  |
| Pressure Angle:   |
| 20.0000 degrees   |
| Distance Between Body Face And Protruding Hub End:                            |
| 0.221 inches first end  |
| Face Width:   |
| 0.104 inches  |
| Bore Diameter:  |
| 0.125 inches both ends  |
| Hub Style Designator:   |
| Plain first end   |
| Hub Diameter:   |
| 0.187 inches first end  |
| Material:   |
| Steel comp 303 hub  |
| Material Specification:   |
| Qq-s-764, type 303, cond a federal specification single material response hub |
| Surface Treatment:  |
| Passivate hub   |
| Style Designator:   |
| Protruding hub  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| Δ27300  |