NSN 3020-00-420-7615

Bevel Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-420-7615

| Body Style: | | | | | | |
|--|--|--|--|--|--|--|
| Plain, solid | | | | | | |
| Pitch Diameter: | | | | | | |
| 2.3330 inches | | | | | | |
| Teeth Quantity: | | | | | | |
| 14 | | | | | | |
| Bore Style: | | | | | | |
| W/ keyway both ends | | | | | | |
| Outside Diameter: | | | | | | |
| 2.600 inches | | | | | | |
| Nominallength: | | | | | | |
| 0.718 inches | | | | | | |
| Teeth Type: | | | | | | |
| Skew | | | | | | |
| Tooth Direction: | | | | | | |
| Right | | | | | | |
| Pressure Angle: | | | | | | |
| 20.0000 degrees | | | | | | |
| Pitch Angle: | | | | | | |
| 24.3125 degrees | | | | | | |
| Distance Between Body Face And Protruding Hub End: | | | | | | |
| 0.130 inches first end | | | | | | |
| Face Width: | | | | | | |
| 0.680 inches | | | | | | |
| Bore Diameter: | | | | | | |
| 0.838 inches both ends | | | | | | |
| Keyway Width: | | | | | | |
| 0.188 inches both ends | | | | | | |
| Distance From Bore Center To Keyway Bottom: | | | | | | |
| 0.463 inches both ends | | | | | | |
| Hub Style Designator: | | | | | | |
| Plain first end | | | | | | |
| Hub Diameter: | | | | | | |
| 1.000 inches first end | | | | | | |
| Material: | | | | | | |
| Steel comp 1010 | | | | | | |
| Material Specification: | | | | | | |
| Astm-a576 assn standard single material response | | | | | | |
| Style Designator: | | | | | | |
| Peripheral face, front hub protruding | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |

NSN 3020-00-420-7615

Bevel Gear - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A27300