

View Online at <https://aerobasegroup.com/nsn/3020-00-421-4463>

**Body Style:**

Webbed, offset, solid

**Pitch Diameter:**

3.6250 inches

**Teeth Quantity:**

87

**Bore Style:**

W/counterbore counter bore, second end

**Backlash Designation:**

Grade b

**Outside Diameter:**

3.707 inches

**Tooth Form:**

Standard

**Pressure Angle:**

20.0000 degrees

**Distance Between Body Face And Protruding Hub End:**

1.181 inches first end

**Face Width:**

0.250 inches

**Bore Diameter:**

2.000 inches counter bore, second end

**Counterbore Depth:**

0.5250 inches counter bore, second end

**Counterbore Diameter:**

2.1200 inches counter bore, second end

**Hub Style Designator:**

3 steps first end

**End Length:**

0.380 inches first end

**Precision Classification:**

Quality number 11

**End Diameter:**

2.526 inches first end

**First Step Length:**

0.493 inches first end

**First Step Diameter:**

2.410 inches second end

**Second Step Length:**

0.163 inches first end

**Second Step Diameter:**

2.670 inches first end

**Third Step Length:**

0.141 inches first end

**Third Step Diameter:**

3.190 inches first end

**Special Features:**

Loc 0.530 in. From 1st end bore increase to 2.380 in. Diameter by 0.850 in. Lg

**Material:**

Aluminum alloy 6061 and copper alloy 642

**Material Specification:**

Qq-a-250/11 federal specification 1st material response or qq-b-679 federal specification 2nd material response

**Style Designator:**

Protruding hubs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A27300